



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
 22.09.1999 Bulletin 1999/38

(51) Int. Cl.<sup>6</sup>: **G06K 9/00**

(21) Application number: 99301951.2

(22) Date of filing: 15.03.1999

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE**  
 Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Wang, John Y. A.**  
**Mountain View, California 94040 (US)**

(74) Representative:  
**Powell, Stephen David et al**  
**WILLIAMS, POWELL & ASSOCIATES**  
**4 St Paul's Churchyard**  
**London EC4M 8AY (GB)**


(30) Priority: 16.03.1998 US 39990

(71) Applicant:  
**Hewlett-Packard Company**  
**Palo Alto, California 94304 (US)**

(54) **A person identifier and management system**

(57) A person identifier and management system (10) includes a face image database (13) that stores the face feature data of each of a number of face images and the person-identifying data associated with each of the face images. A camera (23) is also included in the person identifier and management system (10) for capturing an input face image. A face analysis system (12) is then coupled to the camera (23) and the image data-

base (13) to extract the face feature data of the input face image and to compare the face feature of the input face image with that of each of the face images stored in the database (13) such that the person-identifying data of any stored face image similar to the input face image can be retrieved from the image database (13).



**Figure 5**

## Description

[0001] The present invention pertains to image processing and information management. More particularly, this invention relates to a person identifier and management system that can retrieve person-identifying information from a database based on an input face such that the input face can be identified.

[0002] As is known, human nature typically shows that people want to be recognized by others. Thus, it is important for people to recognize and recall the names of other people they have previously met or acquainted during meetings, social functions, or other occasions. Not recognizing the person before you may affect you adversely. For example, if a superior or employer does not recognize or cannot recall the name of an inferior or employee, it may give the inferior/employee the impression that the supervisor/employer does not care about the inferior/employee, or the inferior/employee is not important in the organization. In addition, if a business person cannot recognize or recall the name of a business counterpart from another organization, it may affect the business dealing or potential business dealing with the organization that business counterpart represents.

[0003] However, for people who have a relatively large number of casual acquaintances, association of faces with names is a difficult memory game. In addition, some people are just not good at recognizing or recalling names of formal acquaintances, especially when the formal acquaintances have only been briefly introduced to you. Change of environment may also cause problems for people to recognize or recall names of others. For example, a person will have more difficulty in recognizing people initially if the person is surrounded by a large number of strangers (e.g., in a new office building).

[0004] With the advance of computer and image processing technologies, it is now possible to store an image in a computer system. This can be done using a digital camera to capture an image. In addition, a scanner can be used to convert a printed image into digital form. The digital image includes image pixels (or dots) arranged in a matrix. The data for each image pixel are then stored in the computer. The digital image can be retrieved for display from the computer.

[0005] This allows a face image database to be built in a computer system that can help the user to manage the acquaintances' information. The face image database typically stores a number of face images and the person-identifying information associated with each of the stored images. The person-identifying information is typically a text information that identifies the face. The person-identifying information in text format may include name, contact information, date and occasion of last meeting or all the prior meetings. When the user retrieves a face image from the database, the person-identifying information associated with that image is

also retrieved from the database. When the person-identifying information is displayed with the associated face image, the user can then recognize the face and recall the name of the face.

[0006] However, searches within this face image database is still nearly impossible. In order to identify a desired face image stored in the computer based on an input face image, the prior art typically causes the computer to compare the image pixel data of the input face image with the corresponding pixel data of each of the images stored in the computer. The comparison typically takes a very long time to complete and uses a lot of system resources (e.g., memory and communication bandwidth). This is because the computer has to compare each image pixel data of the input face image with the corresponding image pixel data of each of the stored face images. A match occurs when each pixel data of the input face image is similar the corresponding pixel data of a stored face image. Using this method, unless the two compared images are extremely similar, it is very difficult to find a match between any two face images. This is especially true because noise and other positional errors may be introduced into the image data when the input face image is captured.

[0007] One feature of the present invention is to help a user recall or recognize people the user has previously met.

[0008] Another feature of the present invention is to allow retrieval of personal-identifying information from a database in accordance with an input face image.

[0009] A further feature of the present invention is to provide a person identifier and management system that searches for similar faces of an input face in a face image database such that person-identifying information associated with the similar faces can be retrieved from the database to identify the input face.

[0010] A still further feature of the present invention is to provide a personal person identifier and management system that is portable, personal, and easy to use.

[0011] A person identifier and management system is described. The person identifier and management system includes an image database that stores face feature data of each of a number of face images and person-identifying data associated with each of the face images. An image capturing system is also included for capturing an input face image. A face analysis system is then coupled to the image capturing system and the image database to locate and retrieve the person-identifying data of any stored face image similar to the input face image from the image database. The face analysis system does this by, for example, extracting the face feature data of the input face image and comparing the face feature data of the input face image with that of each of the face images stored in the database.

[0012] A method of retrieving person-identifying information from a face image database based on an input face image includes the step of extracting face feature data from the input face image. The face feature data of

the input face image is then compared with that of a number of face images stored in the database. Each of the stored face images includes the person-identifying information that identifies the respective face image. If the face feature data of one of the stored face images matches that of the input face image, then the person-identifying information of that stored face image is retrieved from the image database to identify the input face image.

**[0013]** Other features and advantages of the present invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

Figure 1 shows the structure of a person identifier and management system that implements one embodiment of the present invention.

Figure 2 illustrates the perspective view of the person identifier and management system of Figure 1 as a portable, personal, and hand-held system in accordance with one embodiment of the present invention.

Figure 3A is a front view of the personal person identifier and management system of Figure 2.

Figure 3B shows the top view of the personal person identifier and management system of Figure 2.

Figure 4 shows the analysis system of the person identifier and management system of Figure 1.

Figure 5 shows the input/output system of the person identifier and management system of Figure 1.

Figure 6 shows the data format for each of the face images stored in the profile database of the person identifier and management system of Figure 1.

**[0014]** Figure 1 shows a person identifier and management system 10 that implements one embodiment of the present invention. As will be described in more detail below, the person identifier and management system 10 allows a user to retrieve person-identifying or face-identifying information of a person from a profile database (or face image database) 13 of the person identifier and management system 10 based on the person's face inputted to the person identifier and management system 10 such that the person can be identified or recognized by the user of the person identifying system 10. This means that the person identifier and management system 10 can use the input face image to search the profile database 13 for matching face or faces and their associated face-identifying or person-identifying data so that the input face can be identified or recognized.

**[0015]** As will be described in more detail below, the person identifier and management system 10 includes the profile database 13. The profile database 13 stores a number of face images and their associated face-identifying or person-identifying data. The profile database 13 stores the pixel data of each of the face images.

In addition, the profile database 13 also stores the face feature data of each of the face images. The face feature data of a face image is associated with that face image in the profile database 13. The person-identifying data of each of the face images is also associated with the respective face image in the profile database 13.

**[0016]** In addition to the profile database 13, the person identifier and management system 10 also includes an analysis system 12 that (1) detects if an input image of the person identifier and management system 10 contains a face image and (2) extracts the face feature data from the input image if the input image is detected to contain a face. The input image is supplied by an input/output system 11 connected to the analysis system 12. The input/output system 11 is also used for outputting the person-identifying data retrieved from the profile database 13.

**[0017]** The analysis system 12 accesses the profile database 13 with the extracted face feature data of the input face image to locate the matching face feature data in the profile database 13. When there is a match between the face feature data of the input face image and the face feature data of one or more stored face images, the person-identifying data of the matching face images are retrieved from the profile database 13. This allows the user of the person identifier and management system 10 to identify or recognize the input face image. The person identifier and management system 10 will be described in more detail below, also in conjunction with Figures 1-6.

**[0018]** Figure 1 shows in block diagram form the structure of the person identifier and management system 10. The person identifier and management system 10 can be a single stand-alone device or implemented in a computer or computer-enabled system. If the person identifier and management system 10 is implemented in a computer system, the computer system can be a personal computer, a notebook computer, a mini-computer, a hand-held computer, a personal communicator, a workstation, a network computer, a server computer, or a mainframe computer.

**[0019]** As can be seen from Figure 1, the person identifier and management system 10 includes the input/output system 11, the analysis system 12, and the profile database 13. The input/output system 11 is connected to the analysis system 12. The analysis system 12 is then connected to the profile database 13. The input/output system 11 is used provide the input and output functions for the person identifier and management system 10. The analysis system 12 is used to detect a face from an input image and to use the face feature data extracted from the input face image to search the profile database 13 in order to identify the input face image.

**[0020]** The profile database 13 stores a number of face images and their face feature data and person-identifying or face-identifying data. The face feature data and the person-identifying data are fully searcha-

ble in the database 13. The face feature data and its creation will be described in more detail below, also in conjunction with Figures 1 and 4. The person-identifying data can be a text data, an image data, and a combination of text and image data. The person-identifying data of a face image may include the name of the person, affiliation or employment of the person, and time and occasion of last meeting or all of the previous meetings with the person. The employment information may include name of the company the person is currently working for, the title and position of the person within the company. In addition, the person-identifying data may also include other information, such as telephone and fax numbers and/or e-mail address, the name of the third person who introduced the person, and/or other types of person-identifying information.

**[0021]** Each of the digital face images stored in the profile database 13 is, for example, in the pixel matrix format. This means the profile database 13 stores the pixel data of each of the stored face images. In addition, the face feature data and the person-identifying data of each face image are associated with or linked to the respective face image stored in the profile database 13. The face feature data and the person-identifying data of a face image are, however, not necessarily physically stored adjacent to the respective face image in the profile database 13. The profile database 13 can be implemented and accessed using known database technologies. Figure 6 shows the logical memory map 100 for the face images stored in the profile database 13.

**[0022]** As can be seen from Figure 6, the logical memory map 100 of the profile database 13 of Figure 1 includes a number of entries 101 through 100n, each for storing one digital face image. Each entry (e.g., the entry 101) includes a face feature data field (e.g., the face feature data field 101a), a person-identifying data field (e.g., the person-identifying data field 101b), and the image pixel data field (e.g., the pixel data field 101c). The pixel data field of each entry stores the pixel data (i.e., the image data) of a face image stored in the profile database 13. The face feature data field of each entry stores the face feature data of a face image stored in the database 13 and the person-identifying data field of each entry stores the person-identifying data of a face image stored into the database 13. The face feature data field of an entry is associated with or linked to the face image of that entry. The person-identifying data field of an entry is also associated with or linked to the face feature data of that entry.

**[0023]** Referring back to Figure 1, the input/output system 11 is used to input face images to the person identifier and management system 10. In addition, the input/output system 11 is also the output means of the person identifier and management system 10 for data output. For example, the input/output system 11 outputs the person-identifying data of a matching face stored in the person identifier and management system 10 by

displaying or printing the person-identifying data. The input/output system 11 may include a number of input and output devices or modules. For example, the input/output system 11 may include a display that displays the input face image to be searched in the profile database 13 for matching faces. The display also displays any person-identifying data retrieved from the profile database 13. In addition, the input/output system 11 may also include a digital camera that captures the input face image. The digital camera may be replaced, for example, with a scanner. Moreover, the input/output system 11 may include a text input device (e.g., keyboard or touch sensitive screen with handwriting recognition capabilities) that allows input of text person-identifying data into the profile database 13. Figure 5 shows one implementation of the input/output system 11 of Figure 1, which will be described in more detail below.

**[0024]** As can be seen from Figure 5, the input/output system 11 includes an I/O controller 51 connected to a number of I/O devices 52 through 56. The function of the I/O controller 51 is to control various input/output activities of the input/output system 11. The I/O controller 51 is implemented using known I/O controller technologies.

**[0025]** The I/O devices 52-56 include a camera 52, a display 53, a scanner 54, a sensitive pen 55, and other I/O devices 56. The camera 52 can be any known digital camera. The display 53 can be any known computer or TV display. In one embodiment, the display 53 is a touch sensitive screen display that allows text and/or graphics input using a sensitive pen. In this case, the touch sensitive screen display may have an embedded keyboard or may have a handwriting recognition system. All of the I/O devices 52-55 can be implemented using known technologies.

**[0026]** The other I/O devices 56 may include a keyboard, a printer, and a modem or network adaptor for network communications. All the other I/O devices 56 are known I/O devices. Although Figure 5 show I/O devices 52-56 for the input/output system 11, the input/output system 11 may include more or fewer than I/O devices 52-56. For example, the input/output system 11 may not include the scanner 54.

**[0027]** Referring back to Figure 1, the analysis system 12 of the person identifier and management system 10 is used to detect the face from the input face image supplied from the input/output system 11. In addition, the analysis system 12 extracts face feature data from the detected face in the input face image. The analysis system 12 then uses the extracted face feature data to search the profile database 13 for matching face feature data stored. If matching face feature data is located in the profile database 13, then the analysis system 12 retrieves the person-identifying data associated with the matching face feature data stored in the profile database 13. When the user of the person identifier and management system 10 views the retrieved person-

identifying data, the user is able to recognize or identify the input face image.

[0028] If no matching face feature data is found in the profile database 13, it means that none of the stored face images in the profile database 13 is similar to the input face image. In this case, the analysis system 12 makes such indication to the user. The user can then have the option of storing the input face image in the profile database 13, along with the associated face feature data and the person-identifying data. Before storing the input face image into the profile database 13, the analysis system 12 asks the user to input the person-identifying data of the input face image via the input/output system 11. The structure and function of the analysis system 12 will be described in more detail below, also in conjunction with Figure 4.

[0029] Referring to Figure 4, the analysis system 12 includes a user interface 41, a search engine 42, and a face detection and feature extraction system 43. The user interface 41 is connected to the search engine 42 and the face detection and feature extraction system 43. The search engine 42 is also connected to the face detection and feature extraction system 43. Each of the components 41-43 is a functional module and can be implemented by software, hardware, and firmware.

[0030] The user interface 41 is an interactive user interface that is part of an interactive window interface. The user interface 41 includes a window (not shown) that displays the input face image and the retrieved person-identifying data. In addition, the user interface 41 also includes a number of command or function buttons that can be activated using a user input device (e.g., mouse or sensitive pen). The user interface 41 may also include a touch sensitive screen keyboard or a hand writing recognition system. The user interface 41 can be implemented using any known technology.

[0031] The face detection and feature extraction system 43 receives the input face image from the user interface 41. The face detection and feature extraction system 43 detects if the input face image contains any face. The detection system 43 also detects the eye locations of the face in the input face image. The system 43 then uses the eye location data to compute the face feature data of the detected face. The face feature data are also referred to as face coefficient data.

[0032] In one embodiment, the detection system 43 uses neural network-based face detection technology to detect the face in the input face image. The neural network-based face detection scheme is disclosed in a publication entitled HUMAN FACE DETECTION IN VISUAL SCENES, by H. Rowley (har@cs.cmu.edu), S. Baluja (baluja@cs.cmu.edu), and T. Kanade (tk@cs.cmu.edu) in November 1995. The publication is available from Carnegie Mellon University's Internet site at "www.ius.cs.cmu.edu/IUS/har2/har/www/CMU-CS-95-158R/." Alternatively, other known face detection technologies may be used. For example, a face detection scheme described in U.S. Pat. No. 5,164,992, dated

November 17, 1992, and entitled FACE RECOGNITION SYSTEM can be employed.

[0033] When the detection system 43 uses the neural network-based face detection scheme, the detection system 43 detects if the input face image contains any face by first applying a set of neural network-based filters to the image. The filters examine each location in the image at several scales, looking for locations that might contain a face (i.e., looking for eye locations). The detection system 43 then uses an arbitrator to combine the filter outputs. The arbitrator is used to merge detections from individual filters and eliminate overlapping detections. Using the neural network-based face detection technology makes the face detection robust, relatively fast, and detect most faces. In addition, it allows the detection system 43 to detect different kinds of faces with different poses and lightings.

[0034] Once a face is detected, the face detection and feature data extraction system 43 computes the face feature data of the detected face. In one embodiment, the face detection and feature extraction system 43 computes the face feature data of the detected face using a face feature extraction technology described in the above-mentioned U.S. Pat. No. 5,164,992. Alternatively, other known face feature extraction schemes may be used.

[0035] The face feature extraction process by the system 43 is done by first normalizing, warping (i.e., rotating and scaling), and masking the face to produce a reference face that has a set of predetermined eye locations. This means that through normalizing, warping, and masking of the detected face, the eyes of the detected face are mapped into the predetermined eye locations of the reference face. This is done by translating, scaling, and rotating the detected face and by adjusting the brightness and contrast of the detected face. In other words, this is to standardize or normalize the detected face. This is disclosed in the above-mentioned U.S. Pat. No. 5,164,992.

[0036] Then the system 43 projects the standardized face into an Eigen-face space to compute the face coefficients or face feature data of the detected face. This is also disclosed in the above-mentioned U.S. Pat. No. 5,164,992.

[0037] After the face detection and feature extraction system 43 extracts the face feature data, the extracted face feature data is then sent to the search engine 42. The search engine 42 then accesses the profile database 13 (Figure 1) with the extracted face feature data. This is to find and locate any face feature data stored in the profile database 13 that matches or is similar to the extracted face feature data.

[0038] The search engine 42 uses the extracted face feature data to search for face images stored in the profile database 13 having similar face feature data. The search engine 42 compares the extracted face feature data with each stored face feature data to output similarity scores based on the predetermined similarity meas-

ure. In one embodiment, the similarity measure includes a set of thresholds and the face feature data includes a set of values. The comparison of the corresponding values of two face feature data yields differences between the values of the two data. The differences are then compared against their corresponding thresholds. A similarity score is obtained based on how many of the differences are less or more than the thresholds. The search engine 42 can be any kind of known search engine.

**[0039]** The search engine 42 then retrieves the person-identifying data associated with the matching face feature data (i.e., the similar faces) from the profile database 13. In one embodiment, the search engine 42 retrieves both the person-identifying data and the pixel data of the similar images for display after a search. In another embodiment, the search and engine 42 selectively retrieves the person-identifying data of the similar images in accordance with their similarity scores.

**[0040]** When there is no matching face feature data in the profile database 13 and the input face image is to be stored in the profile database 13, the face detection and feature extraction system 43 extracts the face feature data from the input face image and associates the face feature data with the input face image before storing the image and the face feature data into the profile database 13. In addition, the face detection and feature extraction system 43 receives the person-identifying data of the input face image from the user interface 41 before storing the pixel data and the face feature data of the input face image into the profile database 13. The person-identifying data of the input face image is also associated with the face feature data of the input face image in the profile database 13.

**[0041]** Referring back to Figure 1, the person identifier and management system 10 can be a portable personal system that can be easily carried around by the user of the system 10. For example, the person identifier and management system 10 can be a hand-held personal system. Alternatively, the person identifier and management system 10 can also be a non-portable system. Figure 2 is a perspective view of a hand-held portable personal person identifier and management system 20 that implements one embodiment of the person identifier and management system 10 of Figure 1. Figures 3A and 3B show the front and top views of the hand-held portable personal person identifier and management system 20.

**[0042]** As can be seen from Figures 2 and 3A-3B, the hand-held portable personal person identifier and management system 20 includes a touch sensitive screen display 22 that allows display of the input face image 24 and the retrieved person-identifying data 25 and a digital camera 23 that is an integrated part in the hand-held portable personal person identifier and management system 20. The digital camera 23 is used to capture the input face image 24. In addition, the hand-held portable personal person identifier and management system 20

also include a writing tool 21 that allows input into the hand-held portable personal person identifier and management system 20 via the touch sensitive screen display 22.

**[0043]** In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident to those skilled in the art that various modifications and changes may be made thereto without departing from the scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

## Claims

1. A person identifier and management system (10), comprising:

(A) an image database (13) that stores face feature data of each of a plurality of face images and person-identifying data associated with each of the face images;

(B) an image capturing system (11, 23) that captures an input face image;

(C) a face analysis system (12) coupled to the image capturing system (11, 23) and the image database (13) to locate and retrieve the person-identifying data of any stored face image similar to the input face image from the image database (13).

2. The person identifier and management system (10) of claim 1, wherein the face analysis system (12) locates and retrieves the person-identifying data from the image database (13) by extracting the feature data of the input face image and comparing the face feature data of the input face image with that (101a) of each of the face images stored in the face image database (13).

3. The person identifier and management system (10) of claim 1 or 2, wherein the person identifier and management system (10) is a portable personal person identifier and management system, wherein the face analysis system (12) further comprises

(I) a face detection and feature extraction system (43) that detects the input face image and extracts the face feature data from the input face image;

(II) a search engine (42) that compares the face feature data of the input face image with that of the face images stored in the image database (13).

4. The person identifier and management system (10) of any of claims 1-3, wherein the face analysis system (12) further comprises a user interface (41) that

allows the input face image and the person-identifying data to be displayed on a display and that allows a user to input and associate the person-identifying data with a face image displayed.

5

5. The person identifier and management system (10) of claims 1-4, wherein the image capturing system is an integrated digital camera.
6. The person identifier and management system (10) of claim 5, wherein the person-identifying data includes name, affiliation, and time and occasion of meetings.
7. The person identifier and management system (10) of claim 6, further comprising a display (22) that displays the person-identifying data along with the input face image.
8. The person identifier and management system (10) of claim 7, wherein the display (22) is a touch screen display that also allows input of the person-identifying data into the face image database (13).

25

30

35

40

45

50

55




Figure 1






Figure 2






Figure 3A



*Figure 3B*

*Figure 4*





Figure 5

100



LOGICAL MEMORY MAP OF THE IMAGE DATABASE

Figure 6

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 944 019 A3**

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
05.09.2001 Bulletin 2001/36

(51) Int Cl.7: G06K 9/00, G06F 17/30

(43) Date of publication A2:  
22.09.1999 Bulletin 1999/38

(21) Application number: 99301951.2

(22) Date of filing: 15.03.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventor: Wang, John Y. A.  
Mountain View, California 94040 (US)

(74) Representative: Powell, Stephen David et al  
WILLIAMS, POWELL & ASSOCIATES  
4 St Paul's Churchyard  
London EC4M 8AY (GB)


(30) Priority: 16.03.1998 US 39990

(71) Applicant: Hewlett-Packard Company,  
A Delaware Corporation  
Palo Alto, CA 94304 (US)

### (54) A person identifier and management system

(57) A person identifier and management system (10) includes a face image database (13) that stores the face feature data of each of a number of face images and the person-identifying data associated with each of the face images. A camera (23) is also included in the person identifier and management system (10) for capturing an input face image. A face analysis system (12)

is then coupled to the camera (23) and the image database (13) to extract the face feature data of the input face image and to compare the face feature of the input face image with that of each of the face images stored in the database (13) such that the person-identifying data of any stored face image similar to the input face image can be retrieved from the image database (13).



**Figure 5**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 1951

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	BRZEZOWSKI S J ET AL: "Integrated portable system for suspect identification and tracking" SURVEILLANCE AND ASSESSMENT TECHNOLOGIES FOR LAW ENFORCEMENT, BOSTON, MA, USA, 19-20 NOV. 1996, vol. 2935, pages 24-35, XP000957348 Proceedings of the SPIE - The International Society for Optical Engineering, 1997, SPIE-Int. Soc. Opt. Eng, USA ISSN: 0277-786X * the whole document *	1,7	G06K9/00 G06F17/30
A	---	1-8	
A	MANN S: "Smart clothing": wearable multimedia computing and "personal imaging" to restore the technological balance between people and their environments" PROCEEDINGS ACM MULTIMEDIA 96, PROCEEDINGS OF 4TH MULTIMEDIA CONFERENCE, BOSTON, MA, USA, 18-22 NOV. 1996, pages 163-174, XP001002292 1996, New York, NY, USA, ACM, USA ISBN: 0-89791-871-1 * abstract *	1-8	TECHNICAL FIELDS SEARCHED (Int.Cl.6)  G06K G06F
A	WO 96 29674 A (LAU TECHNOLOGIES) 26 September 1996 (1996-09-26) * page 2, line 19 - page 3, line 20 * * page 4, paragraph 1 * * page 4, line 38 - page 5, line 8 * --- -/--	1-8	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>22 June 2001</b>	Examiner <b>Granger, B</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons  & : member of the same patent family, corresponding document	

EPO FORM 1503 03 82 (P04C01)





European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 1951

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	<p>PENTLAND A ET AL: "VIEW-BASED AND MODULAR EIGENSPACES FOR FACE RECOGNITION" PROCEEDINGS OF THE COMPUTER SOCIETY CONFERENCE ON COMPUTER VISION AND PATTERN RECOGNITION, US, LOS ALAMITOS, IEEE COMP. SOC. PRESS, 21 June 1994 (1994-06-21), pages 84-91, XP000515825 ISBN: 0-8186-5827-4 * abstract *</p> <p>-----</p>	1-8	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
THE HAGUE		22 June 2001	Granger, B
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>&amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P44C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 1951

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

22-06-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9629674 A	26-09-1996	AU 5135996 A	08-10-1996
		CA 2215942 A	26-09-1996
		CN 1184542 A	10-06-1998
		EP 0815531 A	07-01-1998
		JP 11502344 T	23-02-1999
<hr/>			

EPO FORM P0489

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82